

# Technical specs

## AMAZONES5 - AMAZONE S5 SRA (AMAZOS5NO)

**Name:**

PVC SAFETY AMAZONE BOOT - S5 SRA

**Size:**

36 - 37 - 38 - 39 - 40 - 41 - 42 - 43 - 44 - 45 - 46 - 47

**Colour:**

Black



**Description :**

Upper : PVC. No Lining. No Insole.

Outsole : Injected PVC - Nitrile .

**Materials:**

see description

**Instructions for use:**

Safety boots for general use.

Safety boots S5 SRA, class 2, knee-height boots. Footwear with a protective toe cap providing protection against shocks equivalent to 200 joules and against crushing risks under a maximum 1500daN load. Puncture-proof sole with anti-penetration insert (P). Footwear with antistatic properties (A), and energy absorbing heel (E). Slip resistant Footwear provided for Hard industrial floors, tiled type, for indoor use (SRA). Cleated outsole, with resistance to fuel oil.

**Limits to use:**

The PANOPLY® guarantee can only be applied optimal-condition shoes, being used without adding up any accessories likely to generate a change in protection, or it cannot be applied when its use is not specified in the current instructions for use. Do not use this equipment out of its usage specifications defined in the instructions above. Check footwear integrity before each use.

**Instructions for storage:**

Keep in its original packing away from light and humidity. Do not store these boots near a source of heat.

**Instructions for cleaning / maintenance:**

Clean under water or with a neutral detergent, with a wet sponge. Brush the outsole after use. To remove clay and dust, use a no metallic brush.

After any use, leave unpacked shoes in a ventilated place away from any heat source.

**Performances :**

Class II Safety boots S5 SRA, class 2, Comply with the requirements of the European Directive 89/686/EEC, specially for ergonomics, harmlessness, comfort, airing and flexibility and with the requirements of the European standards EN ISO 20344:2004 / A1:2007 and EN ISO 20345:2004 / A1:2007

- **EN ISO 20345:2004/A1:2007** Specifications on safety shoes for professional use.  
S5 : Additional special requirements  
SRA : Resistance to slipping



**DELTA PLUS GROUP**

La Peyrolière - B.P. 140 - 84405 APT Cedex - France  
www.deltaplus.fr

