

# Technical specs

## FRONTERAS3 - FRONTERA S3 SRC (FRONTS3MA)

### Name:

FULL GRAIN LEATHER BOOTS - S3 HRO CI HI SRC

### Size:

36 - 37 - 38 - 39 - 40 - 41 - 42 - 43 - 44 - 45 - 46 - 47 - 48

### Colour:

Brown



### Description :

Boots range 4 X 4 INDUSTRY. Upper : Full grain leather with coated leather scuffcap. Lining : Polyamide Cambrelle absorbing. Insole : Removable preformed - Polyamide Cambrelle on EVA. Midsole : Injected - Panorubber®. Outsole : Rubber Nitrile. Anti-penetration insert and safety toe cap : Composite.

### Materials:

See description

### Strong points:

Shock-resistant and crushproof composite toe cap 200 j. Energy absorber heel. Oil resistant outsole. Composite puncture-proof sole. Slip resistant cleated outsole for loose soil. Anti-static protection. Contact heat resistant outsole. Water resistant material. Heat-insulated sole. Sole insulated against cold.

### Instructions for use:

General use safety footwear for smooth and oily industrial-type floors or loose ground, for indoor or outdoor use against intermediate risks equipped with a puncture-proof sole and a protective toe cap providing protection against shocks equivalent to 200 joules and against crushing risks under a maximum 15 kN load. S3\*: safety footwear with closed back, antistatic protection, energy absorbing heel and puncture-proof sole, water-resistant upper and studded sole. HRO\*: contact-heat resistant outsole, 300°C for 60s, HI\*: Heat-insulated sole, CI\* : sole insulated against cold. Outsole with resistance to fuel oil (FO).

### Limits to use:

The DELTAPLUS® guarantee can only be applied optimal-condition shoes, being used without adding up any accessories likely to generate a change in protection, or it cannot be applied when its use is not specified in the current instructions for use. Not to be used for protection against further hazards than defined above. Not to be used within the scope of any other field of activity than that defined in the above-mentioned instructions. A removable insock is provided with this footwear. Testing was carried out on the footwear with the insock in place. Consequently, this footwear must be worn with the insock in place. It may only be replaced by a comparable insock supplied by Delta Plus. This footwear contains no substances known to cause allergic reactions in people with allergic sensitivities.

### Instructions for storage:

To be stored in its original packing in a dry place, sheltered from sun light.

### Instructions for cleaning / maintenance:

After any use, leave unpacked shoes in a ventilated place away from any heat source. To remove clay and dust, use a non metallic brush. For stains, use a wet cloth with soap if necessary. To shoe polishing, use a standard product.

### Performances :

Fulfill the requirements of the European Directive 89/686, specialfor ergonomics, harmlessness, comfort, airing and flexibility



**DELTA PLUS GROUP**

La Peyrolière - B.P. 140 - 84405 APT Cedex - France  
www.deltaplus.fr



# Technical specs

## **FRONTERAS3** - FRONTERA S3 SRC (*FRONTS3MA*)

and fulfill therequirements of the European standards EN ISO 20344:2011 and EN ISO 20345:2011 S3\* HRO\* HI\* CI\* SRC (Resistance to slipping on Ceramic and Steel floors, for all types of hard floors for multiple uses indoors or outdoors).

- **EN ISO 20345:2011** Personal protective equipment - Safety footwear.  
**S3 HRO HI CI** : Additional special requirements  
**SRC** : Resistance to slipping