

# Technical specs

## HAR11

**Name:**

FULL BODY HARNESS 1 PT BACK ATTACHMENT

**Size:**

L/XXL Adjustable

**Colour:**

Orange / Black



**Description :**

Full body harness made of 45 mm wide red polyester straps with

- back attachment
- two corrosion-resistant parachute buckles at the thigh level, to open and easily adjust the harness.

**Materials:**

Straps : polyester  
Corrosion-resistant buckles

**Instructions for use:**

This harness is recommended for all types of height interventions (frames, roofs, glass roofs, scaffoldings, travelling cranes, cranes), for simple works, of short period or occasional. A harness must be strapped to the body as tight as possible but not excessively to allow total freedom of movements to the user.

**Limits to use:**

Do not use this harness out of its usage specifications defined in the instructions above. Replace the harness if its protective quality becomes doubtful. After a fall, return the harness for inspection to the manufacturer or one of his qualified representatives. Schedule harness control every 12 months, either by the manufacturer or by a qualified representative. A full body harness and a lanyard do not constitute a fall arrest system.

**Instructions for storage:**

The harness must be hung up in a temperate, dry and ventilated room away from sun rays and rodents.

**Instructions for cleaning / maintenance:**

Brush with water and soap. The harness will be then wiped with a dry cloth and hung up in a ventilated room. Coat metallic parts with vaseline oil soaked cloth. Bleaching agents and detergents are strictly forbidden. The equipment must always be inspected before use. Check especially:

- Straps : no start of cutting, of burning, of rusting, of abnormal narrowing.
- Sewing : no visible damage - Metallic elements : no distortion or oxidation.

To make sure that the karabiners work correctly.

**Performances :**

This harness complies with the European directive 89/686, notably regarding design, manufacture and test methods, and with EN361 standard.

CE 0082